



LED FLUSHMOUNT COMFORT

► **DESIGN & OPTIONS** - LED FLUSHMOUNT COMFORT has a modern, multipurpose design along with a stylish look and efficient smooth lighting. It features a durable painted metal base, a PS diffuser for even illumination with no glare, triac dimming and an energy-efficient LED driver with stable light output and economic power consumption. It is also CCT selectable, allowing you to set the color temperature to 2,700K, 3,000K, 3,500K, 4,000K or 5,000K with a simple switch.

► **INSTALLATION** - Installation is quick and easy: just drive the screws into the outlet box, connect the wires, and place the lamp body on the screws. Multiple mounting holes allow it to be mounted to a variety of junction box sizes. All installation accessories are included. Refer to install instructions for detailed steps.

► **APPLICATION** - This fixture provides bright, yet smooth lighting for your family room, bedroom, hallway, corridor, or any other common area in your living space. It can be used as an additional light to an already existing ceiling light as well. It is also Damp location rated.

► **ENERGY SAVINGS & EFFICIENCY** - With a lifespan of 25,000 hours, these fixtures are made to last decades under normal operation! This fixture can cut your electric bill by up to 80% instantly and will save you a significant amount of money in its lifetime.

► **CERTIFICATION & WARRANTY** - Buy with confidence: ASD provides a 5-year limited warranty along with ETL certification to guarantee top quality products and safety!


Catalog number	
Notes	
Type	




AFINA



LOFT BLACK



LOFT NICKEL



STONE



DIAMOND



MYSTERY



WOOD



HONEY



Model	Size	Watts	Voltage	Dimmable	Lumens	CCT	Finish	Dimensions (LxWxH)
ASD-LFC-LF-16D28-AC-BK	16 inch	28W	120 V	TRIAC	1,325/1,446/1,553/1,623/1,576 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Black	15-3/8" x 15-3/8" x 3-15/16"
ASD-LFC-LF-16D28-AC-NK	16 inch	28W	120 V	TRIAC	1,325/1,446/1,553/1,623/1,576 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Nickel	15-3/8" x 15-3/8" x 3-15/16"
ASD-LFC-SN-16D28-AC	16 inch	28W	120 V	TRIAC	1,758/1,896/2,036/2,126/2,053 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	White	16-15/16" x 16-15/16" x 3-3/4"
ASD-LFC-AF-20D42-AC	20 inch	42W	120 V	TRIAC	2,158/2,315/2,497/2,638/2,468 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Black	19-1/8" x 19-1/8" x 3-9/16"
ASD-LFC-LF-20D42-AC-BK	20 inch	42W	120 V	TRIAC	2,028/2,181/2,356/2,475/2,474 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Black	19-5/16" x 19-5/16" x 4-5/16"
ASD-LFC-LF-20D42-AC-NK	20 inch	42W	120 V	TRIAC	2,028/2,181/2,356/2,475/2,474 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Nickel	19-5/16" x 19-5/16" x 4-5/16"
ASD-LFC-SN-20D42-AC	20 inch	42W	120 V	TRIAC	2,818/3,026/3,263/3,430/3,206 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	White	20-13/16" x 19-5/16" x 4-1/8"
ASD-LFC-DD-20D42-AC	20 inch	42W	120 V	TRIAC	2,818/3,026/3,263/3,430/3,206 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	White	19-5/16" x 19-5/16" x 3-9/16"
ASD-LFC-MY-20D42-AC	20 inch	42W	120 V	TRIAC	2,818/3,026/3,263/3,430/3,206 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	White	19-1/2" x 19-1/2" x 3-3/16"
ASD-LFC-WD-20D42-AC	20 inch	42W	120 V	TRIAC	1,824/1,957/2,112/2,230/2,098 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Wood	19-1/8" x 19-1/8" x 3-9/16"
ASD-LFC-HN-20D42-AC	20 inch	42W	120 V	TRIAC	2,138/2,249/2,544/2,372/2,381 lm	5CCT (2,700/3,000/3,500/4,000/5,000 K)	Gold	18-7/8" x 18-7/8" x 4-3/4"

For most up-to-date spec sheets please refer to asd-lighting.com

ASD LIGHTING CORP

E-mail: orders@asd-lighting.com | Web site: www.asd-lighting.com





LED FLUSHMOUNT COMFORT


PRODUCT SPECIFICATIONS:

Construction & Materials					
Housing	Iron				
Lens	PS				
Finish color	Black, Nickel, White, Wood, Gold				
Weight	ASD-LFC-LF-16D28-AC-BK	1.1 lb (2.4 kg)	ASD-LFC-SN-20D42-AC	2.9 lb (1.3 kg)	
	ASD-LFC-LF-16D28-AC-NK		ASD-LFC-DD-20D42-AC	3.3 lb (1.5 kg)	
	ASD-LFC-SN-16D28-AC	0.9 lb (2 kg)	ASD-LFC-MY-20D42-AC		
	ASD-LFC-AF-20D42-AC	3.1 lb (1.4 kg)	ASD-LFC-WD-20D42-AC	3.1 lb (1.4 kg)	
	ASD-LFC-LF-20D42-AC-BK	3.3 lb (1.5 kg)	ASD-LFC-HN-20D42-AC		
	ASD-LFC-LF-20D42-AC-NK				
Environmental system					
Work environment	Suitable for Damp Locations				
Operating temperature	-4°F to 104°F (-20°C to 40°C)				
L-70 Life	> 25,000 hrs				
Optical system					
Luminous flux	ASD-LFC-LF-16D28-AC-BK	1,325/1,446/1,553/1,623/1,576 lm	ASD-LFC-SN-20D42-AC	2,818/3,026/3,263/3,430/3,206 lm	
	ASD-LFC-LF-16D28-AC-NK		ASD-LFC-DD-20D42-AC		
	ASD-LFC-SN-16D28-AC	1,758/1,896/2,036/2,126/2,053 lm	ASD-LFC-MY-20D42-AC	1,824/1,957/2,112/2,230/2,098 lm	
	ASD-LFC-AF-20D42-AC	2,158/2,315/2,497/2,638/2,468 lm	ASD-LFC-WD-20D42-AC		
	ASD-LFC-LF-20D42-AC-BK	2,028/2,181/2,356/2,475/2,474 lm	ASD-LFC-HN-20D42-AC		2,138/2,249/2,544/2,372/2,381 lm
	ASD-LFC-LF-20D42-AC-NK				
Color temperature	5CCT (2,700/3,000/3,500/4,000/5,000 K)				
CRI	> 80				
Electrical system					
Input voltage	120 V				
Max input current	0.4 A				
Inrush current (Action time)	20 A (0.5 S)				
AC input range	min 108V max 132V				
Off state power	0W				
Power consumption	ASD-LFC-LF-16D28-AC-BK	28W	ASD-LFC-SN-20D42-AC	42W	
	ASD-LFC-LF-16D28-AC-NK		ASD-LFC-DD-20D42-AC		
	ASD-LFC-SN-16D28-AC		ASD-LFC-MY-20D42-AC		
	ASD-LFC-AF-20D42-AC	42W	ASD-LFC-WD-20D42-AC		
	ASD-LFC-LF-20D42-AC-BK		ASD-LFC-HN-20D42-AC		
	ASD-LFC-LF-20D42-AC-NK				
Power factor	> 0.9				
Output voltage	126 V				
Max output current	270 mA				
Surge protection DM/CM	1.5 kV / 3.6 kV				
LED driver class	Class 1				
Dimming range					
10-100%					
Dimming compatible controls					
Brand	Legrand	Leviton	Lutron		
Models	ADTH700RMTU	DW6HD	TGCL-153PH	DVCL-153P	
	ADTP703TU	DZ6HD	MACL-153M	DV-603P	
	RHCL453P	IG4805			
Regular and voluntary certifications					
5-year limited warranty		ETL certified 5022592			

PACKAGE CONTENTS:


Description	Q-ty
LED Flushmount Comfort	1
Wire nut (A)	3
Screw (B)	2
Box	1

A

B

PACKAGE CONTENTS:

Description	Q-ty
LED Flushmount Comfort	1
Wire nut (A)	3
Screw (B)	2
Box	1



For most up-to-date spec sheets please refer to asd-lighting.com

ASD LIGHTING CORP

E-mail: orders@asd-lighting.com | Web site: www.asd-lighting.com





LED FLUSHMOUNT COMFORT

INSTALLATION GUIDE

IMPORTANT SAFETY INFORMATION:

Please read all the instructions below before installation.

- ▶ Make sure that the supply voltage corresponds to the rated product voltage.
- ▶ The product must be installed by a qualified electrician in accordance with the National Electrical Code and corresponding local codes.
- ▶ If the product is damaged, do not use it.

⚠ WARNING

RISK OF PERSONAL INJURY – READ and follow all WARNINGS and installation instructions. Keep or give to the owner for future reference.


Risk of cuts: Wear gloves to prevent cuts or abrasions when removing from carton, handling, installing, and maintaining this product.

Risk of electric shock: This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Risk of Fire: Minimum 194°F supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor.


ASD® assumes no responsibility for claims arising out of improper or careless installation or handling of this product.

ELECTRICAL SCHEMATIC DIAGRAM:



INSTALLATION STEPS:

1. Remove the lens by rotating it clockwise.
2. Attach the two screws to the outlet box. Connect the wires: Black to Black, White to White, Ground to Ground. Secure the connection with wire nuts. Carefully tuck all the wires back into the outlet box.
3. Choose either 2,700K, 3,000K, 3,500K, 4,000K or 5,000K with a simple switch. Attach the lens and rotate it counter-clockwise to secure it to the fixture.



ORDERING INFORMATION

Model	UPC	Pcs. per carton	Carton size	Carton weight	GTIN 14
ASD-LFC-LF-16D28-AC-BK	810050737869	4	20.5" x 18.1" x 18.3"	17.6 lb	10810050737866
ASD-LFC-LF-16D28-AC-NK	810050737876	4	20.5" x 18.1" x 18.3"	17.6 lb	10810050737873
ASD-LFC-SN-16D28-AC	810050737883	4	20.5" x 18.1" x 18.3"	16.6 lb	10810050737880
ASD-LFC-AF-20D42-AC	810050737159	4	21.8" x 18.1" x 22"	24 lb	10810050737156
ASD-LFC-LF-20D42-AC-BK	810050737135	4	21.4" x 19.7" x 21.7"	24 lb	10810050737132
ASD-LFC-LF-20D42-AC-NK	810050737142	4	21.4" x 19.7" x 21.7"	24.3 lb	10810050737149
ASD-LFC-SN-20D42-AC	810050737173	4	23" x 20.3" x 23.5"	23.1 lb	10810050737170
ASD-LFC-DD-20D42-AC	810050737838	4	21.8" x 22" x 18.1"	24 lb	10810050737835
ASD-LFC-MY-20D42-AC	810050737845	4	22" x 22" x 15.7"	24 lb	10810050737842
ASD-LFC-WD-20D42-AC	810050737166	4	21.8" x 18.1" x 22"	24 lb	10810050737163
ASD-LFC-HN-20D42-AC	810050737852	4	21.4" x 21.7" x 23.6"	23.1 lb	10810050737859

For most up-to-date spec sheets please refer to asd-lighting.com

ASD LIGHTING CORP

E-mail: orders@asd-lighting.com | Web site: www.asd-lighting.com

