



PRO series

- ▶ **DESIGN** LED AREA LIGHT WITH Q-BASE AND PHOTOCELL is extremely efficient with a 170lm/W output. With 10kV surge protection and a 0-10V dimmable driver. The built-in motion sensor base allows you to install the microwave or PIR motion sensor. Integrated photocell switches the fixture on at night time. The photocell can be disabled with built-in switch. The fixture is designed to operate on 120-277V or 200-480V with a power adjustable option.
- **VARIETY** The fixture comes in rectangular or round shape and is available in White, Black, Silver or Bronze finishes.
- ▶ PHOTOCELL The built-in Dusk to Dawn Photocell will automatically activate/deactivate the fixture depending on the time of day. The photocell can be disabled with on-off switch.
- ▶ COLOR AND POWER SELECTABLE You can choose between 3,000 K warm white, 4,000 K cool white, and 5,000 K daylight white color temperatures.
- ▶ INSTALLATION The fixture can be mounted to a junction box or directly to a wall. Perfect commercial or industrial solution for outdoor security lighting, wall perimeter lighting, garages, large backyards, warehouses, hotels, and many other applications. It is also Wet Locations rated.
- ▶ ADVANTAGES With calculated lifespan up to 145 000 hours, these fixtures are made to last decades under normal operation! ASD provides a 5-year limited warranty along with UL and DLC Premium certifications to guarantee top quality products and safety!

Catalog number	
Notes	
Туре	



















Model	Power	Sensor base	Voltage	Dimming	Lumens	сст	Finish	Dimensions	Option	Feature	Certification
						LSB5B-PR0 170lm/W					
ASD-LSB5B-PR0-150WH	100/120/150W	3-pin	120-277V	0-10V	25,480lm	3CCT (3,000/4,000/5,000K)	White	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-150SL	100/120/150W	3-pin	120-277V	0-10V	25,480lm	3CCT (3,000/4,000/5,000K)	Silver	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-150BR	100/120/150W	3-pin	120-277V	0-10V	25,480lm	3CCT (3,000/4,000/5,000K)	Bronze	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-150BK	100/120/150W	3-pin	120-277V	0-10V	25,480lm	3CCT (3,000/4,000/5,000K)	Black	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-200BR	100/150/200W	3-pin	120-277V	0-10V	33,541lm	3CCT (3,000/4,000/5,000K)	Bronze	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-240BR	150/200/240W	3-pin	120-277V	0-10V	40,208lm	3CCT (3,000/4,000/5,000K)	Bronze	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-300WH	200/240/300W	3-pin	120-277V	0-10V	52,312lm	3CCT (3,000/4,000/5,000K)	White	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-300SL	200/240/300W	3-pin	120-277V	0-10V	52,312lm	3CCT (3,000/4,000/5,000K)	Silver	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-300BR	200/240/300W	3-pin	120-277V	0-10V	52,312lm	3CCT (3,000/4,000/5,000K)	Bronze	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PR0-300BK	200/240/300W	3-pin	120-277V	0-10V	52,312lm	3CCT (3,000/4,000/5,000K)	Black	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5B-PRO-500BR	300/400/500W	3-pin	120-277V	0-10V	84,993lm	3CCT (3,000/4,000/5,000K)	Bronze	29-7/16" x 12-3/16" x 2-3/4"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
					L	SB5BHV-PRO HIGH VOLTAGE 1	70lm/W				
ASD-LSB5BHV-PRO-150BR	100/120/150W	3-pin	200-480V	0-10V	25,063lm	3CCT (3,000/4,000/5,000K)	Bronze	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5BHV-PRO-200BR	100/150/200W	3-pin	200-480V	0-10V	35,081lm	3CCT (3,000/4,000/5,000K)	Bronze	12-5/16" x 11-5/16" x 2-7/16"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5BHV-PRO-240BR	150/200/240W	3-pin	200-480V	0-10V	41,003lm	3CCT (3,000/4,000/5,000K)	Bronze	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5BHV-PRO-300SL	200/240/300W	3-pin	200-480V	0-10V	52,156lm	3CCT (3,000/4,000/5,000K)	Silver	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5BHV-PRO-300BR	200/240/300W	3-pin	200-480V	0-10V	52,156lm	3CCT (3,000/4,000/5,000K)	Bronze	16-9/16" x 12-3/16" x 2-1/2"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
ASD-LSB5BHV-PRO-500BR	300/400/500W	3-pin	200-480V	0-10V	86,367lm	3CCT (3,000/4,000/5,000K)	Bronze	29-7/16" x 12-3/16" x 2-3/4"	Photocell	Cord 3.9 ft	UL(E473804), DLC Premium
						SENSORS AND REMOTE					
ASD-09MW-WH	Microwave motion	on sensor 3	pin white					2-1/8" x 2-1/8" x 1-5/16"	-	-	-
ASD-09MW-BK	Microwave motion	on sensor 3	pin black					2-1/8" x 2-1/8" x 1-5/16"	-	-	-
ASD-09IR-WH	Infrared motion s	sensor 3pin	39 ft white					2-1/8" x 2-1/8" x 1-11/16"	-	-	-
ASD-09IR-BK	3K Infrared motion sensor 3pin 39 ft black							2-1/8" x 2-1/8" x 1-11/16"	-	-	-
ASD-09IR50-WH	Infrared motion s	sensor 3pin	50 ft white					2-1/8" x 2-1/8" x 1-11/16"	-	-	-
ASD-09MW-NLS-WH	Microwave motion	on sensor N	ILS 3pin white					2-1/8" x 2-1/8" x 1-3/8"	-	-	-
ASD-09IR-NLS-WH	Infrared motion s	sensor NLS	3pin 39 ft whit	te				2-1/8" x 2-1/8" x 1-11/16"	-	-	-
ASD-06RC	Remote control for motion sensor							5-11/16" x 1-3/4" x 13/16"	-	-	-

For detailed luminous flux information please refer to Annex 1, page 10.









PRO series

TECHNICAL PARAMETERS:

Model	Max input current	Inrush current	Work environment	Operating temperature	Power factor	Surge protection	Housing	Lens	CRI
			LSB58	3-PR0 170lm/W					
ASD-LSB5B-PR0-150WH	1,7A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>80
ASD-LSB5B-PR0-150SL	1,7A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>80
ASD-LSB5B-PR0-150BR	1,7A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-150BK	1,7A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-200BR	2,2A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-240BR	2,7A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-300WH	3,4A	A08	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PRO-300SL	3,4A	80A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-300BR	3,4A	A08	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PRO-300BK	3,4A	A08	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
ASD-LSB5B-PR0-500BR	5,6A	60A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	6kV	Aluminum	PC	>70
			LSB5BHV-PR0	HIGH VOLTAGE 170lm/W					
ASD-LSB5BHV-PRO-150BR	0,9A	78A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70
ASD-LSB5BHV-PRO-200BR	1,1A	130A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70
ASD-LSB5BHV-PRO-240BR	1,4A	58A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70
ASD-LSB5BHV-PRO-300SL	1,7A	96A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70
ASD-LSB5BHV-PRO-300BR	1,7A	96A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70
ASD-LSB5BHV-PRO-500BR	2,8A	130A	Wet location	-40°F to 122°F(-40°C to 50°C)	>0,9	10kV	Aluminum	PC	>70

EFFECTIVE PROJECTED AREA:

Model		Fixture quantity											
LSB5B-PR0	Single	Double 180°	Double 90°	Triple 90°	Triple 120°	Quad 90°							
150-200W	1.16 ft²	2.32 ft ²	2.32 ft ²	3.48 ft ²	3.48 ft ²	4.64 ft ²							
240-300W	1.686 ft²	3.372 ft²	3.372 ft ²	5.058 ft ²	5.058 ft ²	6.744 ft ²							
500W	2.98 ft ²	5.96 ft ²	5.96 ft ²	8.94 ft ²	8.94 ft ²	11.92 ft²							

DIMMING COMPATIBLE CONTROLS:

Brand	Lutron	Leviton	Eaton
	DVCL-153P	IP710-DLZ	SF10P
Models	NTSTV-DV	DDMX1	
	NTFTV	DDL06	

PACKAGE CONTENTS:

Description	Quantity
LED Area Light with Q-base and photocell	1
Box	1








PRO series

ACCESSORIES (sold separately):



ACCESSORY COMPATIBILITY LIST:

Models	Accessories	Microwave motion sensor 3pin ASD-09MW	Infrared motion sensor 3pin ASD-09IR, ASD-09IR50	Microwave motion sensor smart 3pin ASD-09MW-NLS	Infrared motion sensor smart 3pin ASD-09R-NLS	Arm mounting bracket ASD-AM-LSB5	Adjustable arm mounting bracket for 150-300W ASD-AMR-LSB5	Adjustable arm mounting bracket for 500W ASD-AMR2-LSB	Slip fitter bracket for 150-300W ASD-SF-LSB5	Slip fitter bracket for 500W ASD-SF2-LSB	Tenon bracket ASD-TN	Dual bull tenon bracket ASD-82BT	Triple bull tenon bracket ASD-B3BT	Full trunnion mounting bracket for 150-300W ASD-TR-LSB5	Floodlight mounting bracket for 150-200W ASD-FM1-LSB5B	Floodlight mounting bracket for 240-300W ASD-FM2-LSB5B	Floodlight mounting bracket for 500W ASD-FM3-LSB5B	Wall mounting bracket ASD-WMB-LSB	Spill shield for 150-200W ASD-SPS-LSB5	Spill shie ld for 240-500W ASD-SPS2-LSB5	Clear lens for 150-200W ASD-L2A-LSB5B, ASD-L4A-LSB5B; ASD-L5A-LSB5B	60° Floodlight Clear lens for 150-200W ASD-LFLA-LSB5B	Clear lens for 240-500W ASD-L2B-LSB5B,ASD-L4B-LSB5B,ASD-L5B-LSB5B	60° Floodlight Clear lens for 240-500W ASD-LFLB-LSB5B
	150W	•	•	•	•	•	•		•			•	•	•	•			•	•		•	•		
100 10050 /	200W	•	•	•	•	•	•		•			•	•	•	•			•	•		•	•		
ASD-LSB5B/ ASD-LSB5BHV	240W	•	•	•	•	•	•		•			•	•	•		•		•		•			•	•
AGD EGBOBITY	300W	•	•	•	•	•	•		•			•	•	•		•		•		•			•	•
	500W	•	•	•	•			•		•	•						•			•			•	•

CERTIFIED







PRO series

MOTION SENSOR INFORMATION

REMOTE CONTROL ASD-06RC sold separately



Button	Remarks	Button	Remarks	Button	Remarks
ON/OFF ON/OFF	Turn the sensor ON/OFF.	м н Mounting height	Adjust detection area/sensitivity levels according to real installation situations, higher or lower.	♣ Up	The main functional buttons to adjust the factors to desired level.
Auto Auto	Enter "sensor mode" and perform previous settings.	Send Send	Memorize and send out the previous setting of individual parameters.	→ Down	Press + - button to dim light directly auto in non-detection mode.
Reset Reset	Enter "sensor mode" and perform the default settings.	Detection range	Also known as "sensitivity", 100 % means the highest sensitivity and longest distance. Use this button and the + - buttons to adjust.	ССТ CCT selectable	Not applicable to this product.
Scenes Scenes	Shows current settings saved in remote.	Daylight sensor	The preset lux level at which motion will be detected. Use this button and the + - buttons to adjust.	Power Power	Adjust brightness in both ON/OFF mode & sensor mode, minimum 10%, max 100%, each time this button is pressed it changes by 5%.
Start Start	Press this to begin scene setup.	Stand-by dimming	After hold time, the light will dim from 100 % to optional standby dimming levels. Use this button and the + - buttons to adjust.	Reserved button	Not applicable to this product.
Memory Memory	Saves the scene settings.	(9) Hold time	The period that light will stay illuminated 100 % after no motion is detected. Use this button and the + - buttons to adjust.	Daylight harvesting	Daylight harvesting function enabled or disabled.
Appy Apply	Applies current scene settings to the fixture.	Stand-by period	The period after holdtime, during which the light keeps standby dimming level. Use this button and the + - buttons to adjust.	Test button	Press this button to test the sensor; it will temporarily change the hold time to 2s. This setting cannot be saved.

Use the ASD-06RC remote control to put the ASD-09-NLS sensor in pairing mode. Point the remote control at the sensor and press the "RESET" button.



Microwave motion

sensor 3pin







control



Infrared motion

sensor 3pin



Aicrowave motion sensor NLS 3pin








ASD-09IR-NLS Infrared motion sensor NLS 3pin

ASD-06RC Remote control or smartphone

MICROWAVE MOTION SENSOR:



- 1. Microwaves can penetrate walls or glass thinner than 0.8" but will be impaired if thicker than 0.8"
- 2. The driver voltage shall be stable and float within 10 %.
- 3. Detection area will be affected by speed of motion, mounting height and movement volume.
- 4. Conduct testing with adequate ambient lighting for best results.
- 5. Dimming performance differs when connected to different drivers; If the driver can't completely turn OFF, sensor can't either
- 6. The first time powered ON sensor, light will be ON 100% for about 10S then dims to standby level

Installation precautions:

- 1. Suitable for ceiling mount installation, adjust sensitivity properly if it's installed on side-wall because
- 2. Make sure the microwave module is completely exposed.
- 3 The detection surface of the sensor module should be installed facing the detection area

Application environment:

- 1. Suitable for indoor application, half/completely outdoor environment conditions might trigger the sensor
- 2. Shall be mounted securely, to avoid any false triggers caused by movement of the fixture itself
- 3. Keep the sensor module away from AC input and DC output to avoid high/low frequency signal

INFRARED MOTION SENSOR:



Mounting height < 39.4 ft (12 m) ceiling mounting (* for ASD-09IR50 < 49.2 ft (15 m))

- 1. The driver voltage shall be stable and float within 10%
- 2. Detection area options may not function as expected because they depend on the Fresnel lens, which physically determines their operation.
- 3. Detection distance performance works better when moving parallel to the sensor as opposed to
- Conduct testing with adequate ambient lighting for best results.
- Dimming performance differs when connected to different drivers; If the driver can't completely turn OFF, sensor can't either.
- 6. The first time powering ON the sensor, light will be ON 100% for about 45S then dims to standby level or OFF.

Installation precautions:

- 1. PIR sensor can't be placed inside any material, fresnel lens must be completely exposed in air.
- 2 Fresnel lens of the PIR sensor must be lower than light fixture.
- 3. Suitable for ceiling mount installation, adjust sensitivity properly if it's installed on a wall because it will become more sensitive.

Application environment:

- Suitable for indoor application, partial/completely outdoor environment conditions might trigger the sensor.
- 2. The PIR sensor is not suitable for environments with sudden changes in temperature or airflow.
- 3. Not suitable environment if there's shelves between the sensor and target area
- 4. Shall be mounted securely, to avoid any false triggers caused by movement of the fixture itself.

Specifications	models: ASD-09MW, ASD-09MW-NLS	models: ASD-09IR, ASD-09IR-NLS	models: ASD-09IR50	Default setting					
Detection area	25 %/50 %/75 %/100 %			100 %					
Hold time	Remote control: 5 s/30 s/1 min/3 min/5 min/10 m	note control: 5 s/30 s/1 min/3 min/5 min/10 min/20 min/30 min Built-in switch: 5 s/1 min/5 min/10 min							
Daylight threshold	2 lux (0.2 fc)/10 lux (0.9 fc)/30 lux (2.8 fc)/50 lux (4.7	x (0.2 fc)/10 lux (0.9 fc)/30 lux (2.8 fc)/50 lux (4.7 fc)/80 lux (7.4 fc)/120 lux (11.2 fc)/200 lux (18.6 fc)/250 lux (23.2 fc)/300 lux (27.9 fc)/350 lux (32.5 fc)/400 lux (37.2 fc)/disable							
Standby period	0 s/10 s/30 s/1 min/5 min/10 min/30 min/60 min/	/10 s/30 s/1 min/5 min/10 min/30 min/60 min/+ ∞							
Standby dimming level	Remote control: 10 %/20 %/30 %/50 % Built-in s	Remote control: 10 %/20 %/30 %/50 % Built-in switch: 0 %/10 %/30 %/50 %							
Operating voltage	10 - 15 V			-					
Operating current	< 30 mA	< 15 mA	< 30 mA	-					
Mounting height	max 49.2 ft (15 m)	max 39.4 ft (12 m)	max 49.2 ft (15 m)	-					
Detection range	≥ 9 ft (3 m)	9.8 - 22.9 ft (3-7 m)		-					
Operating frequency	5.8 GHz ± 75 MHz	-	-	-					
Transmitting power	< 0.3 mW	-	-	-					









PRO series



For ASD-NLS sensors download ASD NLS App and add the fixture to it according to the manual (download manuals and app from the links or scan the QR codes on the right).

ASD NLS is a professional-grade smart control application designed to manage and control lighting fixtures in commercial properties. With ASD NLS, you can conveniently control your lights from your smartphone or PC, anytime and anywhere.

You can group fixtures by rooms, floors and objects, and create schedules based on day and time. You can also grant permanent or temporary permissions to employees and guests with different access levels. Our smart platform enables you to monitor energy usage statistics, view the status of each fixture, and much more.



Desktop manual



Smartphone manual





ASD-09MW-NLS Microwave motion sensor NLS 3pin



ASD-09IR-NLS Infrared motion sensor NLS 3pin



ASD NLS APP download Android



ASD NLS APP download iOS



FIXTURE CONTROL

Set brightness, standby time and dimming level, or apply scenes and schedules



CONTROL **PERMISSIONS**

Give your staff or installers control over the lighting.





SCHEDULING

Set a variety of customizable start / end actions based on time of day and days of the week.



ADVANCED ENERGY CONSUMPTION

Monitor equipment status and receive daily reports.





ADVANCED AREA MANAGEMENT

Create and customize projects for different types of areas, buildings, floors and zones.





PROJECT OVERVIEW

Monitor device status and daily reports












PRO series


WITH DUSK/DAWN FUNCTION:

- With insufficient ambient brightness, sensor turns on light and keeps it at standby dimming level even if there is no motion or presence.
- 2. When sensor detects motion or presence it will bring the light level up to 100 %
- 3. After motion is no longer detected, fixture remains at 100 % for hold time.
- After the preset hold time period, it will dim to the standby dimming level and maintain it indefinitely.
- 5. With sufficient ambient brightness, sensor will turn OFF light automatically




WITH DAYLIGHT DISABLED:

- 1. Sensor turns ON light when motion is detected.
- 2. Light will stay on after detecting motion for the desired hold time.
- 3. Sensor dims light to standby dimming level after hold time if there is still no motion.
- 4. Sensor turns OFF light after standby period.



WITH DAYLIGHT THRESHOLD:

- 1. With sufficient daylight, the light remains OFF even after motion is detected.
- 2. With insufficient daylight, the sensor turns light ON when motion is detected.
- 3. After there's no motion detected, the sensor keeps light ON 100 % for holdtime
- 4. After holdtime, sensor dims light to standby dimming level for standby period. If the standby period has been set as Os, sensor turns light OFF automatically after holdtime.
- The sensor turns OFF light automatically after the standby period when there's no motion detected.



DAYLIGHT HARVESTING:

- 1. When the ambient brightness is lower than the preset lux level, the sensor will automatically turn on the light and adjust the dimming according to changes in ambient brightness. As it gets darker outside, the fixtures will brighten, and as it gets brighter outside, the fixtures will dim.
- 2. When the ambient brightness exceeds the preset lux level, the light will turn OFF





MICROWAVE MOTION SENSOR:


To avoid blocking the microwave emission, the microwave sensor can not be covered with metal materials, be sprayed with a coating of metal components, or have attached metal material or stickers etc.

The distance between the antenna and the glass (dielectric material) should be no less than 0.4 ft when the sensor is within the glass lampshade. Otherwise, the microwave motion sensor will not penetrate the glass easily.

Avoid placing the sensor inside a metal chamber, this may cause a mis-trigger.








The sensor should not be placed in a small confined space. To avoid increasing the sensor detection range or abnormal operation, the sensor solud be kept away from large areas of metal and glass reflectors (separation distance at least 3.3 ft). Reduce the detection area setting.


To avoid affecting the microwave signal transmission, the microwave antenna should be higher than the surrounding metal surface.


Any vibration or movement may trigger the sensor. Ensure the sensor is far from any constant movement.


At least 2 m/6.5 ft distance between microwave sensors;

1.5 m/4.9 ft between the sensor and other wireless devices such as routers to avoid possible radio interference.










DAYLIGHT HARVESTING SETTING:

- 1. Adjust "daylight" value higher than 50lux.
- 2. Preset "standby period" OS.
- 3. Press "daylight harvesting" button on remote control to activate.











PRO series

INSTALLATION GUIDE

IMPORTANT SAFETY INFORMATION:

Please read all the instructions below before installation!

- Make sure that the supply voltage corresponds to the rated product voltage
- The product must be installed by a qualified electrician in accordance with the National Electrical Code and corresponding local codes.
- If the product is damaged, do not use it.

▲ WARNING

Risk of personal injury — read and follow all warnings and installation instructions. Keep or give to the owner for future reference.

Risk of cuts: Wear gloves to prevent cuts or abrasions when removing from carton, handling, installing, and maintaining this product.

Risk of electric shock: This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

Risk of Fire: Minimum 194°F supply conductors. Consult a qualified electrician to ensure correct branch circuit conductor

ASD® assumes no responsibility for claims arising out of improper or careless Installation or handling of this product.

ARM MOUNTING BRACKET:

ASD-AM-LSB5 sold separately


- 1. Open up the door on the arm bracket (1 screw). Install the mounting arm onto the pole (2 bolts). Make sure the silicone gaskets form a tight seal.
- 2. Thread the cord from the fixture through the bracket into the pole and tighten the four M8 screws on the body of the light. Wire in accordance with wiring schematic.
- 3. Close the door on the arm bracket (1 screw).



SLIP FITTER MOUNTING BRACKET:

ASD-SF-LSB5 | ASD-SF2-LSB | sold separately

- 1. Thread the wire through the slip fitter and secure it to the fixture with four screws.
- 2. Make AC connections in accordance with wiring diagram.
- 3. If necessary adjust the fixture angle with the large hex bolt on the side of the slip



The wiring is inside the pole, the side is sealed with a rubber ring and secured with screws, preventing water from getting inside the fixture.

BUILT-IN PHOTOCELL INFORMATION




Specifications	
Light level to turn ON	≤ 80 lux (≤ 7.4 fc)
Light level to turn OFF	≥ 150 lux (≥ 13.9 fc)
Operating temperature	-40°F to 140°F (-40°C to 60°C)

The fixtures with a built-in photocell automatically turn off during daylight hours. Photocell can be easaily deactivated by unscrewing it.

ADJUSTABLE ARM MOUNTING BRACKET:

ASD-AMR-LSB5 | ASD-AMR2-LSB | sold separately

- 1. Open up the door on the arm bracket (1 screw). Install the mounting arm onto the pole (2 bolts). Make sure the silicone gaskets form a tight seal. Choose gasket depending on the shape of the pole (round or flat).
- 2. Thread the cord from the fixture through the bracket into the pole and tighten the four M8 screws on the body of the light. Wire in accordance with wiring schematic.
- 3. Adjust the fixture angle with the large hex bolt on the side of the bracket If necessary.




FLOODLIGHT MOUNTING BRACKET:

ASD-FM1-LSB5B ASD-FM2-LSB5B ASD-FM3-LSB5B

sold separately

- 1. Drill holes on the mounting surface corresponding to the holes in the arm. Attach fixture to bracket with 2 screws.
- 2. Align bracket holes with mounting surface holes and secure with 2 screws.
- 3. Wire in accordance with the wiring schematic. Seal the connections with the back plate of the fixture. Adjust fixture angle as needed.












PRO series

FULL TRUNNION MOUNTING BRACKET:

ASD-TR-LSB5 sold separately


- 1. Drill holes on the mounting surface matching in size to the holes on the arm. Secure the bracket on the wall with screws. Pull wires through mount, secure fixture
- 2. Wire the AC power into the water tight junction box as shown in the wiring schematic diagram. Adjust the screw position to get desired angle when necessary.



WALL MOUNTING BRACKET:

ASD-WMB-LSB sold separately


- 1. Take the bracket apart. Mark and drill two holes in the wall. Insert two dowels into the holes and secure the bracket to the wall using bolts. Then, feed the wire from the bracket into the lamp body. Once properly positioned, use four screws to fasten the lamp body to the gasket.
- 2. Wire according to the electrical schematic diagram.
- 3. Put the bracket on the bolt with screws. Turn the large screws to adjust the angle.



SPILL SHIELD INSTALLATION:

ASD-SPS-LSB5 ASD-SPS2-LSB5 sold separately

- 1. Take out 4 screws from the front of the 150-200W fixture. 6 screws for 240-300W fixture
- 2. Attach the visor to the lens and secure it with new screws. For 150-200W fixtures, use ASD-SPS-LSB5 and 4 bolts; for 240-300W fixtures, use ASD-SPS2-LSB5 and 6 bolts. Ensure all screws are tightened securely.



LENS INSTALLATION:

ASD-L2A-LSB5B ASD-L4A-LSB5B ASD-L5A-LSB5B


ASD-L2B-LSB5B ASD-L4B-LSB5B ASD-LFLA-LSB5B ASD-LFLB-LSB5B

ASD-L5B-LSB5B

sold separately

- 1. Unscrew all screws from the original lens (T3-M) on the housing.
- 2. Install the rubber ring on new lens (T4/T5-M, sold separately).
- 3. Place the lens on the housing and make sure it fits the LEDs correctly
- 4. Tighten all the screws back.

Models	Lens
150W, 200W	1 lens (L2A, L4A, L5A, LFLA)
240W, 300W	1 lens (L2B, L4B, L5B, LFLB)
500W	2 lenses (L4B, L5B, LFLB)




MOTION SENSOR INSTALLATION:

ASD-09MW ASD-09IR ASD-09IR50

ASD-09MW-NLS ASD-09IR-NLS sold separately

- 1. Unscrew the sensor base cap.
- 2. Insert and twist the sensor until it is tight on the base surface.



POWER, COLOR TEMPERATURE AND PHOTOCELL SETTINGS:

- 1. Open knock-out cap in the front panel of the fixture. Select needed power, color temperature and on/off photocell mode with a simple switch.
- 2. Then close the knock-out cap back











PRO series

ORDERING INFORMATION

Model	Product dimensions	Weight	Pcs. Per carton	Carton size	Carton weight	UPC					
	LSB5B-PR0 170lm/W										
ASD-LSB5B-PR0-150BK	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811871					
ASD-LSB5B-PR0-150BR	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811604					
ASD-LSB5B-PR0-150SL	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811835					
ASD-LSB5B-PR0-150WH	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811873					
ASD-LSB5B-PR0-200BR	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811605					
ASD-LSB5B-PR0-240BR	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811606					
ASD-LSB5B-PR0-300BK	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811880					
ASD-LSB5B-PR0-300BR	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811607					
ASD-LSB5B-PR0-300SL	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811881					
ASD-LSB5B-PR0-300WH	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811882					
ASD-LSB5B-PR0-500BR	29 7/16" x 12 3/16" x 2 3/4"	14.1 lbs(6.4kg)	1	31.30" x 14.17" x 4.92"	15.7 lbs	81012811688					
		LSB5BHV-PRO HIGH VOI	LTAGE 170lm/W								
ASD-LSB5BHV-PR0-150BR	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811608					
ASD-LSB5BHV-PR0-200BR	12 5/16" x 11 5/16" x 2 7/16"	5.7 lbs(2.6kg)	1	14.57" x 13.39" x 4.72"	6.8 lbs	81012811689					
ASD-LSB5BHV-PR0-240BR	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811609					
ASD-LSB5BHV-PRO-300BR	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811610					
ASD-LSB5BHV-PR0-300SL	16 9/16" x 12 3/16" x 2 1/2"	7.1 lbs(3.2kg)	1	18.90" x 14.17" x 4.72"	8.2 lbs	81012811612					
ASD-LSB5BHV-PRO-500BR	29 7/16" x 12 3/16" x 2 3/4"	14.1 lbs(6.4kg)	1	31.30" x 14.17" x 4.92"	15.7 lbs	81012811690					

ACCESSORIES:

Model	Product dimensions	Pcs. in middle box"	Middle box size	Middle box weight	Pcs. per carton	Carton size	Carton weight	UPC	GTIN 14 in middle box"	GTIN 14
ASD-09MW-WH	2 1/8" x 2 1/8" x 1 5/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811370	20810128113704	30810128113701
ASD-09MW-BK	2 1/8" x 2 1/8" x 1 5/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811371	20810128113711	30810128113718
ASD-09IR-WH	2 1/8" x 2 1/8" x 1 11/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811369	20810128113698	30810128113695
ASD-09IR-BK	2 1/8" x 2 1/8" x 1 11/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811434	20810128114343	30810128114340
ASD-09IR50-WH	2 1/8" x 2 1/8" x 1 11/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	10.7 lbs	81012811679	10810128116791	20810128116798
ASD-09IR-NLS-WH	2 1/8" x 2 1/8" x 1 11/16"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811375	20810128113759	30810128113756
ASD-09MW-NLS-WH	2 1/8" x 2 1/8" x 1 3/8"	10	5.5" x 2.6" x 11.4"	1.2 lbs	120	17.32" x 11.81" x 11.02"	12.1 lbs	81012811376	20810128113766	30810128113763
ASD-06RC	5 11/16" x 1 3/4" x 13/16"	10	6.3" x 2.9" x 11.4"	0.5 lbs	60	15.75" x 11.81" x 9.29"	24.7 lbs	81012811437	30810128114371	40810128114378
ASD-AM-LSB5-WH	6 13/16" x 6 1/4" x 2 5/16"	-	-	-	10	26.97" x 9.45" x 15.94"	15.4 lbs	81012811847	-	10810128118474
ASD-AM-LSB5-SL	6 13/16" x 6 1/4" x 2 5/16"	-	-	-	10	26.97" x 9.45" x 15.94"	15.4 lbs	81012811846	-	10810128118467
ASD-AM-LSB5-BR	6 13/16" x 6 1/4" x 2 5/16"	-	-	-	10	26.97" x 9.45" x 15.94"	15.4 lbs	81012811620	-	10810128116203
ASD-AM-LSB5-BK	6 13/16" x 6 1/4" x 2 5/16"	-	-	-	10	26.97" x 9.45" x 15.94"	15.4 lbs	81012811845	-	10810128118450
ASD-AMR-LSB5-WH	7 1/4" x 4 15/16" x 6 1/4"	-	-	-	20	27.36" x 16.54" x 13.98"	52.9 lbs	81012811329	-	10810128113295
ASD-AMR-LSB5-SL	7 1/4" x 4 15/16" x 6 1/4"	-	-	-	20	27.36" x 16.54" x 13.98"	52.9 lbs	81012811225	-	20810128112257
ASD-AMR-LSB5-BR	7 1/4" x 4 15/16" x 6 1/4"	-	-	-	20	27.36" x 16.54" x 13.98"	52.9 lbs	81012811224	-	20810128112240
ASD-AMR-LSB5-BK	7 1/4" x 4 15/16" x 6 1/4"	-	-	-	20	27.36" x 16.54" x 13.98"	52.9 lbs	81012811223	-	20810128112233
ASD-AMR2-LSB-WH	9 5/8" x 6 1/4" x 4 5/16"	-	-	-	10	21.38" x 9.57" x 13.43"	30.9 lbs	81012811401	-	10810128114018
ASD-AMR2-LSB-SL	9 5/8" x 6 1/4" x 4 5/16"	-	-	-	10	21.38" x 9.57" x 13.43"	30.9 lbs	81012811333	-	10810128113332
ASD-AMR2-LSB-BR	9 5/8" x 6 1/4" x 4 5/16"	-	-	-	10	21.38" x 9.57" x 13.43"	30.9 lbs	81012811332	-	10810128113325
ASD-AMR2-LSB-BK	9 5/8" x 6 1/4" x 4 5/16"	-	-	-	10	21.38" x 9.57" x 13.43"	30.9 lbs	81012811331	-	10810128113318
ASD-SF-LSB5-WH	7 1/16" x 4 15/16" x 3 1/16"	-	-	-	20	15.51" x 17.72" x 11.14"	35.3 lbs	81012811330	-	10810128113301
ASD-SF-LSB5-SL	7 1/16" x 4 15/16" x 3 1/16"	-	-	-	20	15.51" x 17.72" x 11.14"	35.3 lbs	81012811197	-	10810128111970
ASD-SF-LSB5-BR	7 1/16" x 4 15/16" x 3 1/16"	-	-	-	20	15.51" x 17.72" x 11.14"	35.3 lbs	81012811104	-	20810128111045
ASD-SF-LSB5-BK	7 1/16" x 4 15/16" x 3 1/16"	-	-	-	20	15.51" x 17.72" x 11.14"	35.3 lbs	81012811196	-	10810128111963
ASD-SF2-LSB-WH	10 11/16" x 4 5/16" x 3 3/8"	-	-	-	10	18.43" x 9.25" x 11.77"	35.1 lbs	81012811425	-	10810128114254
ASD-SF2-LSB-SL	10 11/16" x 4 5/16" x 3 3/8"	-	-	-	10	18.43" x 9.25" x 11.77"	35.1 lbs	81012811424	-	10810128114247
ASD-SF2-LSB-BR	10 11/16" x 4 5/16" x 3 3/8"	-	-	-	10	18.43" x 9.25" x 11.77"	35.1 lbs	81012811423	-	10810128114230
ASD-SF2-LSB-BK	10 11/16" x 4 5/16" x 3 3/8"	-	-	-	10	18.43" x 9.25" x 11.77"	35.1 lbs	81012811422	-	10810128114223
ASD-TN-BR	9 7/16" x 3 15/16" x 8 11/16"	-	-	-	5	21.73" x 10.43" x 9.80"	26.2 lbs	81012811680	-	10810128116807
ASD-B2BT	26" x 14 3/16" x 2 3/4"	-	-	-	2	28.43" x 9.92" x 18.50"	28.0 lbs	81012811787	-	10810128117873
ASD-B3BT	37 13/16" x 14 3/16" x 2 3/4"	-	-	-	1	39.45" x 4.41" x 17.32"	19.0 lbs	81012811788	-	-
ASD-TR-LSB5-WH	6 9/16" x 4 7/16" x 1 7/8"	-	-	-	20	14.76" x 10.31" x 12.40"	44.1 lbs	81012811343	-	10810128113431
ASD-TR-LSB5-SL	6 9/16" x 4 7/16" x 1 7/8"	-	-	-	20	14.76" x 10.31" x 12.40"	44.1 lbs	81012811199	-	10810128111994
ASD-TR-LSB5-BR	6 9/16" x 4 7/16" x 1 7/8"	-	-	-	20	14.76" x 10.31" x 12.40"	44.1 lbs	81012811105	-	10810128111055
ASD-TR-LSB5-BK	6 9/16" x 4 7/16" x 1 7/8"	-	-	-	20	14.76" x 10.31" x 12.40"	44.1 lbs	81012811198	-	10810128111987
ASD-FM1-LSB5B-WH	11 7/16" x 6 5/16" x 9 7/8"	-	-	-	10	24.80" x 13.78" x 12.40"	21.2 lbs	81012811839	-	10810128118399
ASD-FM1-LSB5B-SL	11 7/16" x 6 5/16" x 9 7/8"	-	-	-	10	24.80" x 13.78" x 12.40"	21.2 lbs	81012811672	-	10810128116722
ASD-FM1-LSB5B-BR	11 7/16" x 6 5/16" x 9 7/8"	-	-	-	10	24.80" x 13.78" x 12.40"	21.2 lbs	81012811838	-	10810128118382
ASD-FM1-LSB5B-BK	11 7/16" x 6 5/16" x 9 7/8"	-	-	-	10	24.80" x 13.78" x 12.40"	21.2 lbs	81012811671	-	10810128116715
ASD-FM2-LSB5B-WH	12 9/16" x 6 1/16" x 9 5/16"	-	-	-	10	22.64" x 13.98" x 13.98"	27.6 lbs	81012811841	-	10810128118412









Model	Product dimensions	Pcs. in middle box"	Middle box size	Middle box weight	Pcs. per carton	Carton size	Carton weight	UPC	GTIN 14 in middle box"	GTIN 14
ASD-FM2-LSB5B-SL	12 9/16" x 6 1/16" x 9 5/16"	-	-	-	10	22.64" x 13.98" x 13.98"	27.6 lbs	81012811674	-	10810128116746
ASD-FM2-LSB5B-BR	12 9/16" x 6 1/16" x 9 5/16"	-	-	-	10	22.64" x 13.98" x 13.98"	27.6 lbs	81012811673	-	10810128116739
ASD-FM2-LSB5B-BK	12 9/16" x 6 1/16" x 9 5/16"	-	-	-	10	22.64" x 13.98" x 13.98"	27.6 lbs	81012811840	-	10810128118405
ASD-FM3-LSB5B-WH	12 11/16" x 7 1/2" x 12 3/8"	-	-	-	5	14.96" x 13.78" x 13.78"	22.1 lbs	81012811844	-	10810128118443
ASD-FM3-LSB5B-SL	12 11/16" x 7 1/2" x 12 3/8"	-	-	-	5	14.96" x 13.78" x 13.78"	22.1 lbs	81012811842	-	10810128118429
ASD-FM3-LSB5B-BR	12 11/16" x 7 1/2" x 12 3/8"	-	-	-	5	14.96" x 13.78" x 13.78"	22.1 lbs	81012811675	-	10810128116753
ASD-FM3-LSB5B-BK	12 11/16" x 7 1/2" x 12 3/8"	-	-	-	5	14.96" x 13.78" x 13.78"	22.1 lbs	81012811843	-	10810128118436
ASD-WMB-LSB-BR	7 3/16" x 6 1/4" x 3 5/16"	-	-	-	8	18.50" x 15.75" x 13.98"	9.3 lbs	81012811848	-	10810128118481
ASD-SPS-LSB5-BR	11" x 5 7/8" x 2 3/4"	-	-	-	10	15.35" x 12.95" x 12.40"	13.2 lbs	81012811784	-	10810128117842
ASD-SPS2-LSB5-BR	11 15/16" x 8 1/2" x 2 3/4"	-	-	-	10	18.50" x 15.55" x 12.99"	17.6 lbs	81012811785	-	10810128117859
ASD-L2A-LSB5B	10 9/16" x 5 7/8" x 1/2"	-	-	-	30	10.83" x 8.46" x 12.01"	11.7 lbs	81012811613	-	10810128116135
ASD-L4A-LSB5B	10 9/16" x 5 7/8" x 1/2"	-	-	-	30	10.83" x 8.46" x 12.01"	11.7 lbs	81012811615	-	10810128116159
ASD-L5A-LSB5B	10 9/16" x 5 7/8" x 1/2"	-	-	-	30	10.83" x 8.46" x 12.01"	11.7 lbs	81012811617	-	10810128116173
ASD-LFLA-LSB5B	10 9/16" x 5 7/8" x 1/2"	-	-	-	30	10.83" x 8.46" x 12.01"	11.7 lbs	81012811619	-	10810128116197
ASD-L2B-LSB5B	11 7/8" x 8 1/4" x 7/16"	-	-	-	30	11.81" x 10.83" x 12.80"	12.4 lbs	81012811614	-	10810128116142
ASD-L4B-LSB5B	11 7/8" x 8 1/4" x 7/16"	-	-	-	30	11.81" x 10.83" x 12.80"	12.4 lbs	81012811616	-	10810128116166
ASD-L5B-LSB5B	11 7/8" x 8 1/4" x 7/16"	-	-	-	30	11.81" x 10.83" x 12.80"	12.4 lbs	81012811618	-	10810128116180
ASD-LFLB-LSB5B	11 7/8" x 8 1/4" x 7/16"	-	-	-	30	11.81" x 10.83" x 12.64"	12.4 lbs	81012811687	-	10810128116876

ANNEX 1

Model	Watts	3,000 K	4,000 K	5,000 K
ASD-LSB5B-PRO-150WH	100W	17,215 lm	18,124 lm	17,388 lm
ASD-LSB5B-PRO-150SL ASD-LSB5B-PRO-150BR	120W	19,958 lm	20,827 lm	20,520 lm
ASD-LSB5B-PRO-150BK	150W	24,335 lm	25,480 lm	24,141 lm
ASD-LSB5B-PR0-200BR	100W	17,707 lm	18,646 lm	18,135 lm
	150W	24,750 lm	25,904 lm	25,516 lm
	200W	32,410 lm	33,541 lm	33,273 lm
	150W	25,935 lm	26,972 lm	26,433 lm
ASD-LSB5B-PRO-240BR ASD-LSB5BHV-PRO-240BR	200W	32,734 lm	34,305 lm	33,619 lm
	240W	38,197 lm	40,208 lm	39,419 lm
ASD-LSB5B-PR0-300WH	200W	35,785 lm	37,163 lm	37,051 lm
ASD-LSB5B-PRO-300SL ASD-LSB5B-PRO-300BR	240W	41,015 lm	43,620 lm	42,765 lm
ASD-LSB5B-PRO-300BK	300W	48,844 lm	52,312 lm	51,005 lm
	300W	51,980 lm	55,099 lm	54,658 lm
ASD-LSB5B-PRO-500BR	400W	65,693 lm	69,886 lm	69,521 lm
	500W	80,148 lm	84,993 lm	83,326 lm
	100W	18,124 lm	19,082 lm	18,616 lm
ASD-LSB5BHV-PRO-150BR	120W	20,140 lm	20,758 lm	20,446 lm
ASD ESDOBIN THO ISOBIC	150W	23,898 lm	25,063 lm	24,436 lm
	100W	17,463 lm	18,245 lm	18,135 lm
ASD-LSB5BHV-PRO-200BR	150W	25,137 lm	65,181 lm	25,950 lm
	200W	32,410 lm	35,081 lm	34,052 lm
	150W	25,427 lm	26,487 lm	26,225 lm
ASD-LSB5BHV-PRO-240BR	200W	32,474 lm	34,632 lm	34,806 lm
	240W	38,976 lm	41,003 lm	40,224 lm
"ACD LCDEDUV DDO 2000"	200W	33,475 lm	35,274 lm	35,098 lm
"ASD-LSB5BHV-PRO-300SL ASD-LSB5BHV-PRO-300BR"	240W	39,568 lm	41,546 lm	40,923 lm
A3D E3D3D114-11(0-300D1(300W	48,505 lm	52,156 lm	51,208 lm
	300W	53,588 lm	56,707 lm	55,323 lm
ASD-LSB5BHV-PRO-500BR	400W	65,770 lm	71,671 lm	70,404 lm
	500W	80,753 lm	86,367 lm	83,851 lm

