



**LUMINAIRE PHOTOMETRIC TEST REPORT**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 73.38 lm/W			
MODEL		I <sub>max</sub> (cd)	2141	S/MH (C0/180)	0.57
NOMINAL POWER (W)	15	LOR (%)	100.0	S/MH (C90/270)	0.60
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	1023.7	<input type="checkbox"/> UP, DN (C0-180)	0.0, 53.4
NOMINAL FLUX (lm)	1023.69	CIE CLASS	DIRECT	<input type="checkbox"/> UP, DN (C180-360)	0.0, 46.6
LAMPS INSIDE	1	<input type="checkbox"/> up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	120	<input type="checkbox"/> down (%)	100.0	CIBSE SHR MAX	0.65



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity: 65.0%  
 Test Distance: 3.080m [K=1.0000]  
 Remarks:

**ZONAL FLUX DIAGRAM**

ZONAL FLUX DIAGRAM:


°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	1913	1924	1862	1742	1713	1722	1756	1836	0- 10	188.7	188.7	18.4,18.4
20	1034	1171	1042	948.4	861.1	801.3	949.3	1008	10- 20	381.7	570.4	55.7,55.7
30	342.2	492.7	351.0	316.5	248.0	227.8	281.9	314.6	20- 30	283.6	854.1	83.4,83.4
40	59.36	73.51	62.81	58.98	52.67	51.52	55.27	57.81	30- 40	87.76	941.8	92,92
50	34.09	35.09	35.20	34.35	33.48	33.17	33.52	33.60	40- 50	33.59	975.4	95.3,95.3
60	20.17	20.63	20.72	20.30	20.20	20.23	20.20	20.02	50- 60	23.67	999.1	97.6,97.6
70	10.96	11.07	11.12	10.94	11.26	11.58	11.51	11.13	60- 70	15.49	1015	99.1,99.1
80	4.250	3.575	2.682	3.507	4.488	4.370	3.805	4.031	70- 80	7.834	1022	99.9,99.9
90	0.0430	0.0334	0.0391	0.0324	0.0476	0.0487	0.0474	0.0471	80- 90	1.282	1024	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

□ Range: 0 - 90DEG  
 □ Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**LUMINANCE LIMITATION CURVES**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	83	5
80	221	139
75	254	235
70	289	292
65	329	335
60	364	373
55	414	427
50	478	493
45	535	539


C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.11	1.09	1.07	1.09	1.07	1.05	1.05	1.03	1.02	1.01	.00	.99	.98	.97	.96	.94
2.0	1.04	1.00	.97	1.02	.99	.96	.99	.96	.94	.96	.94	.92	.94	.92	.90	.88
3.0	.98	.93	.90	.97	.92	.89	.94	.90	.88	.92	.89	.86	.89	.87	.85	.83
4.0	.92	.87	.84	.91	.87	.83	.89	.85	.82	.87	.84	.81	.85	.83	.80	.79
5.0	.88	.82	.78	.87	.82	.78	.85	.81	.77	.83	.80	.77	.82	.79	.76	.75
6.0	.83	.78	.74	.82	.77	.74	.81	.77	.73	.80	.76	.73	.78	.75	.72	.71
7.0	.79	.74	.70	.79	.74	.70	.77	.73	.70	.76	.72	.69	.75	.72	.69	.68
8.0	.76	.70	.67	.75	.70	.67	.74	.70	.66	.73	.69	.66	.72	.69	.66	.65
9.0	.72	.67	.64	.72	.67	.64	.71	.66	.63	.70	.66	.63	.69	.66	.63	.62
10.0	.69	.64	.61	.69	.64	.61	.68	.64	.61	.67	.63	.60	.67	.63	.60	.59



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

WEC AND CCEC

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Wall Exitance Coefficients (WEC)			
0.0						
1.0	.170 .097 .031	.163 .093 .030	.151 .086 .028	.139 .080 .026	.129 .075 .024	
2.0	.160 .088 .027	.155 .085 .026	.144 .080 .025	.135 .076 .024	.126 .071 .022	
3.0	.151 .080 .024	.146 .078 .024	.137 .074 .023	.129 .071 .022	.121 .067 .021	
4.0	.142 .074 .022	.138 .072 .021	.131 .069 .021	.123 .066 .020	.117 .064 .019	
5.0	.134 .069 .020	.131 .067 .020	.124 .065 .019	.118 .062 .019	.112 .060 .018	
6.0	.127 .064 .018	.124 .063 .018	.119 .061 .018	.113 .059 .017	.108 .057 .017	
7.0	.121 .060 .017	.119 .059 .017	.113 .057 .017	.109 .056 .016	.104 .054 .016	
8.0	.116 .056 .016	.113 .056 .016	.109 .054 .015	.104 .053 .015	.100 .052 .015	
9.0	.110 .053 .015	.108 .053 .015	.104 .052 .015	.100 .050 .014	.097 .049 .014	
10.0	.106 .051 .014	.104 .050 .014	.100 .049 .014	.097 .048 .014	.094 .047 .014	

<input type="checkbox"/> cc	80%	70%	50%	30%	10%	0
<input type="checkbox"/> w	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
<input type="checkbox"/> fc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio		Ceiling Cavity Exitance Coefficients (CCEC)			
0.0	.190 .190 .190	.163 .163 .163	.111 .111 .111	.064 .064 .064	.020 .020 .020	
1.0	.171 .157 .145	.146 .135 .125	.100 .093 .087	.057 .054 .050	.018 .017 .016	
2.0	.155 .133 .114	.133 .114 .098	.091 .079 .069	.052 .046 .040	.017 .015 .013	
3.0	.142 .113 .091	.121 .098 .079	.083 .068 .055	.048 .040 .033	.015 .013 .011	
4.0	.130 .099 .074	.112 .085 .064	.077 .059 .045	.045 .035 .027	.014 .011 .009	
5.0	.121 .087 .061	.104 .075 .053	.072 .052 .038	.042 .031 .022	.013 .010 .007	
6.0	.113 .077 .052	.097 .067 .045	.067 .047 .032	.039 .028 .019	.013 .009 .006	
7.0	.106 .069 .044	.091 .060 .038	.063 .042 .027	.037 .025 .016	.012 .008 .005	
8.0	.100 .063 .038	.086 .055 .033	.060 .038 .023	.035 .023 .014	.011 .007 .005	
9.0	.095 .058 .033	.082 .050 .029	.056 .035 .020	.033 .021 .012	.011 .007 .004	
10.0	.090 .053 .029	.077 .046 .025	.054 .032 .018	.031 .019 .011	.010 .006 .004	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**UGR(Unified Glare Rating) Table**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm										
NAME: ASD-CD-PR-2D15AC-WH					TYPE:			WEIGHT:		
SPEC.:5000K 90					DIM.:			SERIAL No.:		
MFR.: ASD Lighting Corp					SUR.:			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	5.4	6.3	5.6	6.4	6.6	5.4	6.2	5.6	6.4	6.6
3H	6.0	6.7	6.2	6.9	7.1	5.9	6.7	6.2	6.9	7.1
4H	6.2	6.9	6.4	7.1	7.4	6.1	6.9	6.4	7.1	7.3
6H	6.3	7.0	6.6	7.3	7.5	6.2	6.9	6.5	7.1	7.4
8H	6.3	7.0	6.6	7.3	7.5	6.2	6.8	6.5	7.1	7.3
12H	6.3	6.9	6.6	7.2	7.5	6.1	6.8	6.4	7.0	7.3
4H 2H	5.6	6.3	5.9	6.6	6.8	5.6	6.3	5.8	6.5	6.7
3H	6.3	6.9	6.6	7.2	7.5	6.3	6.9	6.6	7.2	7.5
4H	6.6	7.2	6.9	7.5	7.8	6.5	7.1	6.9	7.4	7.7
6H	6.8	7.3	7.2	7.7	8.0	6.6	7.2	7.0	7.5	7.8
8H	6.8	7.3	7.2	7.7	8.1	6.6	7.1	7.0	7.5	7.8
12H	6.8	7.3	7.2	7.6	8.0	6.6	7.0	7.0	7.4	7.8
8H 4H	6.6	7.1	7.0	7.5	7.8	6.6	7.1	7.0	7.4	7.8
6H	7.0	7.4	7.4	7.8	8.2	6.7	7.2	7.2	7.5	8.0
8H	7.0	7.4	7.5	7.8	8.2	6.7	7.1	7.2	7.5	7.9
12H	7.0	7.3	7.5	7.8	8.2	6.7	7.0	7.1	7.4	7.9
12H 4H	6.6	7.1	7.0	7.4	7.8	6.6	7.0	7.0	7.4	7.8
6H	6.9	7.3	7.4	7.7	8.1	6.7	7.1	7.2	7.5	7.9
8H	7.0	7.3	7.5	7.8	8.2	6.7	7.0	7.2	7.5	7.9
Variations with the observer position at spacings:										
S = 1.0H	+ 0.6 / - 0.7					+ 0.7 / - 0.8				
1.5H	+ 1.0 / - 0.5					+ 1.2 / - 0.5				
2.0H	+ 0.6 / - 0.6					+ 0.7 / - 0.7				

CIE Pub.117, 1024 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.1)  
 Area: 0.111111 m2

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**UTILIZATION FACTORS TABLE**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	87	80	76	86	80	76	85	80	76	72
0.80	94	88	84	93	88	84	92	87	84	80
1.00	98	93	89	98	92	89	96	92	88	84
1.25	102	97	94	101	97	93	99	95	92	88
1.50	105	100	97	104	100	96	102	98	95	91
2.00	108	104	100	107	103	100	104	101	98	93
2.50	110	106	103	108	105	102	105	102	100	94
3.00	111	108	105	110	106	104	106	104	102	95
4.00	114	111	108	111	109	107	108	106	104	97
5.00	115	113	111	113	111	109	109	107	106	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**ISOCANDELA DIAGRAM**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:



**AAI Figure**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**ISOLUX DIAGRAM**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**LED Avg.L Report**

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	330
L_0~180 (75) av	258
L_0~180 (85) av	90
L_90~270 (65) av	335
L_90~270 (75) av	253
L_90~270 (85) av	24
L_45 (65) av	332
L_45 (75) av	260
L_45 (85) av	60

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks:

**Planar Illuminance Curve**



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators:  
 Test Date: 2021-11-26

Range: 0 - 90DEG  
 Interval: 1.0DEG  
 Test System: EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity: 65.0%  
 Test Distance: 3.080m [K=1.0000]  
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:119.94V I:0.1180A P:13.950W PF:0.9486 Freq:59.98Hz Lamp Flux:1023.69x1 lm		
NAME: ASD-CD-PR-2D15AC-WH	TYPE:	WEIGHT:
SPEC.:5000K 90	DIM.:	SERIAL No.:
MFR.: ASD Lighting Corp	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) □ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130	2130			
5	2112	2119	2109	2097	2080	2064	2037	2015	1998	1999	2008	2013	2029	2051	2078	2099			
10	1913	1924	1924	1911	1862	1810	1742	1724	1713	1708	1722	1737	1756	1768	1836	1882			
15	1477	1528	1539	1506	1468	1422	1341	1333	1284	1225	1248	1301	1341	1350	1427	1463			
20	1034	1155	1171	1080	1042	1023	948	951	861	785	801	874	949	940	1008	1013			
25	649	804	830	709	643	669	602	612	514	466	480	529	602	578	638	610			
30	342	460	493	419	351	375	316	315	248	220	228	246	282	272	315	302			
35	125	172	191	162	132	143	115	106	87.0	83.2	84.5	93.9	105	105	115	109			
40	59.4	69.4	73.5	68.8	62.8	64.8	59.0	56.5	52.7	51.6	51.5	52.9	55.3	55.7	57.8	57.1			
45	41.9	42.0	42.3	42.5	42.3	42.3	41.8	41.4	41.0	40.6	40.6	40.9	41.2	41.3	41.5	41.2			
50	34.1	34.7	35.1	35.4	35.2	35.0	34.3	33.9	33.5	33.2	33.2	33.3	33.5	33.5	33.6	33.7			
55	26.3	26.8	27.1	27.7	27.2	26.7	26.2	25.9	25.6	25.3	25.2	25.2	25.3	25.3	25.5	25.8			
60	20.2	20.6	20.6	20.9	20.7	20.6	20.3	20.3	20.2	20.1	20.2	20.1	20.2	20.0	20.0	20.0			
65	15.4	15.7	15.7	15.9	15.7	15.7	15.4	15.5	15.6	15.6	15.8	15.7	15.8	15.5	15.5	15.3			
70	11.0	11.1	11.1	11.2	11.1	11.1	10.9	11.1	11.3	11.4	11.6	11.5	11.5	11.2	11.1	10.9			
75	7.30	7.32	7.30	7.01	6.76	6.92	7.23	7.42	7.57	7.71	7.87	7.83	7.77	7.53	7.46	7.31			
80	4.25	4.24	3.58	2.98	2.68	2.92	3.51	4.32	4.49	4.59	4.37	4.00	3.80	3.77	4.03	4.27			
85	0.80	1.30	0.41	0.05	0.05	0.04	0.36	1.26	0.95	1.54	0.87	0.51	0.42	0.41	0.69	1.32			
90	0.04	0.04	0.03	0.03	0.04	0.03	0.03	0.03	0.05	0.05	0.05	0.05	0.05	0.04	0.05	0.05			

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:  
 Test Date:2021-11-26

□ Range: 0 - 90DEG  
 □ Interval: 1.0DEG  
 Test System:EVERFINE GO-SPEX500\_V1 SYSTEM V2.00.421  
 Humidity:65.0%  
 Test Distance:3.080m [K=1.0000]  
 Remarks: